



02 9452-3566

[sales@getpacked.com.au](mailto:sales@getpacked.com.au)

## Electronic Desk Top Label Dispenser

### OPERATING INSTRUCTIONS





产品示意图

## 产品特点

## Machine features

- 使用标签分离机，标签洁净无污染，免破损，不起皱纹，减人增效确保产品质量；
  - 改变传统工作方式，减少人为因素的不良影响，电子控制，自动感应操作，快速分离贴纸，提高粘贴效果，降低工作难度；
  - 适用于自粘标签、条码、防伪、烫金贴纸、封装商标、绝缘材料胶垫、玩具贴纸、生产日期、印刷图案的快速分离粘贴。
- Use label separator, label clean, pollution-free, damage-free, wrinkle-free, reduce people and increase efficiency to ensure productionQuality;
  - Change the traditional way of work, reduce the adverse effects of human factors, electronic control, automatic induction exercise Make, quickly separate stickers, improve the sticking effect.Reduce the difficulty of work;
  - Suitable for fast separation and pasting of self-adhesive labels, bar codes, anti-counterfeiting, stamping stickers, packaging trademarks, insulating mats, toy stickers, production dates and printing patterns.

## 产品功能

## Operation instructions

- 电源：220V/110V,60Hz/50Hz；
- 自动计数0-999999，底纸自动回卷装置，更换方便，做到产量管理自动化。
- 出口版无标签自检停止功能，机器开机延时启动功能(仅限出口版)；
- 操作简单，一机多人使用，适用标签长度：10-150mm，宽度：5-140mm.
- 纸筒内径：25mm-75mm，标签外径：250mm以下；
- 分配速度：1-8米/分钟，一张标签粘贴不到3秒钟；
- 外形尺寸：长210X宽210X高220mm.
- 净重：3.8kg。

- Power supply: 220V/110V, 60Hz/50Hz.
- Automatic counting 0-999999, automatic rewinding device for bottom paper, easy to replace, and automatic production management.
- Export version without label self-check stop function, machine start-up delay start function (export version only).
- Simple operation, multi-user, suitable for label length: 10-150 mm, width: 5-140 mm.
- The inner diameter of the carton is 25 mm -75 mm and the outer diameter of the label is below 250 mm.
- Distribution speed: 1-8 m/min, a label pasted less than 3 seconds.
- Shape size: 210(L)X 210(W)X220(H)mm
- Net weight: 3.8 kg.

## 操作说明

## Operation instructions

- 将标签依图示缠绕；
  - 用压纸杆将底纸卡入卷纸轴；
  - 调节挡纸环使标签靠紧机立板；
  - 按下开电源，按生产需要调节出标速度，细小标签请将速度调慢。
  - 调整感应器的角度，使标签尽可能剥离到最长，以标签边缘剩下2-3mm为最佳。
  - 将计数器清零后即可开始工作。
- Wrap the label according to the figure.
  - Stick the base paper into the reel with an embossing rod.
  - Adjust the paper retaining ring to make the label close to the vertical plate of the machine.
  - Turn on the power supply and adjust the bidding speed according to the production needs. Please slow down the speed of the small labels.
  - Adjust the angle of the sensor so that the label can be stripped to the longest possible length. The best way is to leave 2-3 mm at the edge of the label.
  - The counter can start to work after it is cleared.