Stylus Tapes International



TECHNICAL DATA

4181 DOUBLE SIDED PERM/PEEL ADHESIVE TAPE

DESCRIPTION: A double sided polyester tape coated with a high tack rubber

adhesive (open side) and a low tack removable adhesive

(closed side).

PERFORMANCE Low tack adhesive allows for removal of product from all

FEATURES: surfaces and if required can be re-adhered. High tack adhesive

ensures that adhesive stays on the correct surface so as to

avoid messy transfer of adhesive.

TECHNICAL Adhesive Power: Open Side - 1220 gm/cm

SPECIFICATIONS: Closed Side - 205 gm/cm

Elongation - 65%
Thickness - 0.055mm
Temperature Range - 0ºCto 70ºC

WIDTHS AVAILABLE: 6mm to 1,000mm useable

APPLICATIONS: Ideally suited for the manufacture of protection/scratch pads,

mounting posters and point of sale material, making plastic bags resealable, and core starting in various industries where

slitting and re-rolling of non-adhesive products occurs.

APPROVALS: Adhesive: Open side FDA 175-105

Adhesive: Closed side FDA 177-1010

The above information is given in good faith for guidance only and not specification purposes. All data is based upon average values, the Purchaser shall be responsible for determining the suitability of this product for their purposes.

September 2007.