



7100 SERIES URETHANE OPEN CELL FOAM

DESCRIPTION:

Soft conformable foam with open cells with an aggressive acrylic adhesive. Foam has been approved to Ford Spec SKM-4D9502-A

**PERFORMANCE
FEATURES:**

Foam compresses very easily but recovers quickly; absorbs sound and dampens vibrations. Conforms to irregular size voids. 7100 is RoHS compliant relative to Directive 2002/95/EC.

**TECHNICAL
SPECIFICATIONS:**

Adhesive Power	-	470 gms/cm
Density	-	30kgs/m³
Tensile Strength	-	1.6Kg/cm
Elongation	-	18%
Temperature Resistance	-	-20^o to > 100^oC
Compression Set (50%/22hr/70^oC):		8%

**STANDARD
THICKNESSES:**

7103 - 3mm; 7106 - 6mm; 7109 - 9mm;
7112 - 12mm, 7118 - 18mm.

WIDTHS AVAILABLE:

9mm to 980mm

APPLICATIONS:

Sealing concrete formwork; dust and insect barrier in light fittings; draught seal around doors and windows; sealing around office partitions and ceilings; vibration dampening on instrument panels on machines and equipment and white goods, heaters, fans, air conditioning, automobiles etc.

The above information is given in good faith for guidance only and not specification purposes. All data is based upon average values, the Purchaser shall be responsible for determining the suitability of this product for their purposes.

August 2007